



Mechanical and Fluid Systems

Superelastic Tire

[A viable alternative to the pneumatic tire](#)

Innovators at NASA's Glenn Research center have developed a game changing, non-pneumatic, compliant tire. This innovation, called the Superelastic Tire, was developed for future Mars missions, but is a viable alternative to pneumatic tires here on Earth. This technology represents the latest evolution of the Spring Tire which was invented by NASA Glenn and Goodyear, and inspired by the Apollo lunar tires. The novel use of shape memory alloys capable of undergoing high strain as load bearing components, instead of typical elastic materials, results in a tire that can withstand excessive deformation without permanent damage. Using shape memory alloy as radial stiffening elements can also increase the load carrying capacity of the tire. The Superelastic Tire offers traction equal or superior to conventional pneumatic tires and eliminates the possibility of puncture failures, thereby improving automobile safety. This tire design also eliminates the need for an inner frame which both simplifies and lightens the tire/wheel assembly.

BENEFITS

- **Safe:** Eliminates the possibility of puncture failure
- **Strong:** Can withstand excessive deformation
- **Robust:** Can be configured for high traction on various terrains
- **Simple:** Eliminates the need for air
- **Versatile:** Tire stiffness can be designed to limit energy transferred to vehicle
- **Lightweight:** No inner frame needed for the tire/wheel assembly

technology solution



THE TECHNOLOGY

This NASA Glenn innovation comprises a non-pneumatic, compliant tire utilizing shape memory alloys (mainly NiTi and its derivatives) as load bearing components. These shape memory alloys are capable of undergoing significant reversible strain (up to 10%), enabling the tire to withstand an order of magnitude more deformation than other non-pneumatic tires before undergoing permanent deformation. Commonly used elastic-plastic materials (e.g. spring steels, composites, etc.) can only be subjected to strains on the order of ~ 0.3-0.5% before yielding. Hence, the use of a NiTi shape memory alloy yields a superelastic tire that is virtually impervious to plastic deformation. In addition, the utilization of shape memory alloys provides enhanced control over the effective stiffness as a function of the deformation, providing increased design versatility. For instance, the Glenn Superelastic Tire can be made to soften with increased deflection, reducing the amount of energy transferred to the vehicle during high deformation events. In addition, the use of shape memory alloys in the form of radial stiffeners, as opposed to springs, provides even more load carrying potential and improved design flexibility. This type of compliant tire would allow for increased travel speeds in off-road applications.



The use of shape memory alloy in radial stiffeners provides even more load carrying potential



NASA Glenn's Superelastic Tire is a viable alternative to the pneumatic tire

APPLICATIONS

The technology has several potential applications:

- All-terrain vehicle tires
- Military vehicle tires
- Construction vehicle tires
- Automobile tires
- Heavy equipment tires
- Agricultural vehicle tires
- Aircraft tires

PUBLICATIONS

Patent Pending

National Aeronautics and Space Administration

Technology Transfer Office

Glenn Research Center

21000 Brookpark Road
Cleveland, OH 44135
216-433-3484
grc-techtransfer@mail.nasa.gov

<http://technology.nasa.gov/>

www.nasa.gov

NP-2016-06-2176-HQ

NASA's Technology Transfer Program pursues the widest possible applications of agency technology to benefit US citizens. Through partnerships and licensing agreements with industry, the program ensures that NASA's investments in pioneering research find secondary uses that benefit the economy, create jobs, and improve quality of life.

LEW-18729-1, LEW-19444-1

LEW-TOPS-99

